

## 802 WDP - PROFESSIONAL WET & DRY



BUILDING AND CONSTRUCTION



WINE



CLEANING CONTRACTORS



VEHICLE - TRANSPORT CLEANING



- ✓ Heavy duty steel construction
- ✓ Two powerful by pass motors with independent cooling
- ✓ PPL filter for protection of motors from liquids and foam
- ✓ Floating device to stop the suction when container is full
- ✓ Accessory kit as standard
- ✓ Submerged pump for the discharge of the sucked liquid
- ✓ Possibility of simultaneously suck and discharge liquids



### SUCTION UNIT

Voltage	V - Hz	230 - 50
Power	kW	2,3
Max waterlift	mmH2O	2.500
Max air flow	m <sup>3</sup> /h	360
Suction inlet	mm	50
Noise level (EN ISO 3744)	dB(A)	76



### FILTER UNIT

Filter Type	Bag	
Material - Efficiency	IEC 60335-2-69	Nylon - L
Cleaning system	Manual	



### COLLECTION UNIT

Discharge system	Immersion pump (100lt/min)	
Capacity	lt.	80



### VOLUME

Dimensions	cm	53x59x105h
Weight	kg	50



## SUCTION UNIT

The suction is provided by two by-pass motors, using carbon brushes, operated by independent switches and placed inside a sturdy steel casing, filled with soundproofing material.



## FILTER UNIT

The dust filter is made of a double bag (polyester + nylon) and has a self cleaning system working on the pressure difference principle.



## COLLECTION UNIT

The vacuum cleaner is mounted on a solid steel trolley, provided with a support for hoses when not used, and equipped with oil proof wheels and braking castors.



## OPTIONALS

- ✓ CARTRIDGE OIL FILTRATION KIT DOWN TO 90 MICRON (DISCHARGE)
- ✓ CARTRIDGE OIL FILTRATION KIT DOWN TO 10 MICRON (DISCHARGE)